

Referans Nr.	dx	x L	b	a	e	k	Sıkma Verileri		Tightening Data	Nm	kN	Tightening Data
							Nm	kN				
1590-0606025		x25	15									8
1590-0606040	M6x6	x40	28	5.7	10	4	17	17				11
1590-0606063		x63	40									15
1590-0808032		x32	22									13
1590-0808050	M8x8	x50	35	7.7	12	6	43	32				16
1590-0808080		x80	50									20
1590-1010040		x40	23									35
1590-1010063	M10x10	x63	45	9.7	15	6	79	51				45
1590-1010080		x80	50									60
1590-1010100		x100	60									70
1590-1012050		x50	35									50
1590-1012063		x63	40									60
1590-1012080		x80	55									65
1590-1012100	M10x12	x100	60	11.7	18	7	79	51				75
1590-1012125		x125	75									90
1590-1012160		x160	90									105
1590-1012200		x200	120									120
1590-1212050		x50	35									65
1590-1212063		x63	40									70
1590-1212080		x80	55									80
1590-1212100	M12x12	x100	65	11.7	18	7	141	74				100
1590-1212125		x125	75									110
1590-1212160		x160	100									140
1590-1212200		x200	120									160
1590-1214050		x50	35									80
1590-1214063		x63	45									90
1590-1214080		x80	55									100
1590-1214100	M12x14	x100	65	13.7	22	8	141	74				110
1590-1214125		x125	75									135
1590-1214160		x160	100									160
1590-1214200		x200	120									180
1590-1416063		x63	45									115
1590-1416080		x80	55									140
1590-1416100		x100	65									160
1590-1416125	M14x16	x125	75	15.7	25	9	223	101				180
1590-1416160		x160	100									220
1590-1416200		x200	120									255
1590-1416250		x250	150									300
1590-1616063		x63	45									140
1590-1616080		x80	55									160
1590-1616100		x100	65									190
1590-1616125	M16x16	x125	85	15.7	25	9	354	138				225
1590-1616160		x160	100									270
1590-1616200		x200	120									315
1590-1616250		x250	150									380
1590-1618063		x63	45									170
1590-1618080		x80	55									185
1590-1618100		x100	65									220
1590-1618125	M16x18	x125	85	17.7	28	10	354	138				245
1590-1618160		x160	100									295
1590-1618200		x200	120									340
1590-1618250		x250	150									405
1590-1820080		x80	55									260
1590-1820100		x100	65									290
1590-1820125		x125	85									340
1590-1820160	M18x20	x160	110	19.7	32	12	474	169				390
1590-1820200		x200	125									455
1590-1820250		x250	150									535
1590-1820315		x315	190									650
1590-2020080		x80	55									300
1590-2020100		x100	65									330
1590-2020125		x125	85									380
1590-2020160	M20x20	x160	110	19.7	32	12	679	215				450
1590-2020200		x200	125									535
1590-2020250		x250	160									635
1590-2020315		x315	190									760
1590-2022080		x80	55									345
1590-2022100		x100	65									380
1590-2022125		x125	85									435
1590-2022160	M20x22	x160	110	21.7	35	14	679	215				500
1590-2022200		x200	125									590
1590-2022250		x250	150									695
1590-2022315		x315	190									820

Referans Nr.	dx	x L	b	a	e	k	Sıkma Verileri		Tightening Data	Nm	kN	Tightening Data
							Nm	kN				
1590-2224080		x80	55									465
1590-2224100		x100	65									515
1590-2224125		x125	85									580
1590-2224160	M22x24	x160	110	23.7	40	16	903	266				660
1590-2224200		x200	125									775
1590-2224250		x250	150									805
1590-2224315		x315	190									1050
1590-2424100		x100	70									550
1590-2424125		x125	85									630
1590-2424160		x160	110									725
1590-2424200	M24x24	x200	125	23.7	40	16	1163	310				850
1590-2424250		x250	150									990
1590-2424315		x315	190									1180
1590-2424400		x400	240									1410
1590-2428100		x100	70									660
1590-2428125		x125	85									730
1590-2428160		x160	110									820
1590-2428200	M24x28	x200	125	27.7	44	18	1163	310				950
1590-2428250		x250	150									1090
1590-2428315		x315	190									1300
1590-2428400		x400	240									1530
1590-2428500		x500	290									1800
1590-3036125		x125	80									1280
1590-3036160		x160	110									1440
1590-3036200	M30x36	x200	135	35.6	54	22	2258	493				1620
1590-3036250		x250	150									1880
1590-3036315		x315	200									2150
1590-3036500		x500	300									3010
1590-3642160		x160	100									2260
1590-3642250		x250	175									2890
1590-3642400	M36x42	x400	250	41.6	65	26	3953	719				4010
1590-3642600		x600	340									5900
1590-4248160		x160	100									3550
1590-4248250	M42x48	x250	175	47.6	75	30	6337	986				4530
1590-4248400		x400	250									6160

DIN 787
Ürün Nr. 1590 T-Ayaklı Saplama

- Kalite 12.9
- Siyah kaplama

Product Nr. 1590 T-Slot Bolt

- Quality 12.9
- Black coating


 Loctite
8150

Not: 150 °C üzerindeki ortamlarda sıkma işlemi yapılırken dişlerin üzerine Loctite 8150 kullanılır.

Note: Environments on the 150 °C when clamping action on the thread Loctite 8150 is used.

